

PATENT
Docket No. 1650-005

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Christopher MARSHALL

Entitled: "ENCLOSURE MEMBER, AND MULTI-
LINK CONVEYOR CHAIN"

Serial No. 10/087,459

Filed: March 1, 2002

)
)
) Group Art Unit: 3617
)
) Examiner: Unknown
)
)
)
)

Assistant Commissioner for Patents
U.S. Patent and Trademark Office
Washington, D.C. 20231

SUBMISSION OF CERTIFIED PRIORITY DOCUMENT

In connection with the above-captioned patent application, we hereby submit
the certified copy of United Kingdom patent application Serial No. 0106190.2, filed
on March 14, 2001.

Entry is respectfully requested.

Date: May 30, 2002

Respectfully submitted,


Stephen T. Sullivan
Reg. No. 32,444



Express Mail Label No. EV080009505US

Date of Deposit: May 30, 2002

I hereby certify that the attached Submission of Certified Priority Document is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed Box Missing Parts, Assistant Commissioner for Patents, U.S. Patent and Trademark Office, P.O. Box 2327, Arlington, VA 22202-0327.





INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Andrew Gersey

Dated

- 1 MAR 2002

**CERTIFIED COPY OF
PROPERTY DOCUMENT**

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form.)

THE PATENT OFFICE
A
14 MAR 2001
RECEIVED BY FAX

The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference **GS/AMW/P207104**
2. Patent application number **0106190.2**
(The Patent Office will fill in this part) **14 MAR 2001**
3. Full name, address and postcode of the or of each applicant (underline all surnames) **PENNINE INDUSTRIAL EQUIPMENT LTD
MANOR CROFT HOUSE, COMMERCIAL ROAD
SKELMANTHORPE
HUDDERSFIELD, HD8 9DT**
- Patents ADP number (if you know it) **---**
- If the applicant is a corporate body, give the country/state of its incorporation **UNITED KINGDOM** **8101289001**
4. Title of the invention **ENCLOSURE MEMBER**
5. Name of your agent (if you have one) **URQUHART-DYKES & LORD**
- "Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode) **TOWER HOUSE
MERRION WAY
LEEDS
LS2 8PA
UNITED KINGDOM**
- Patents ADP number (if you know it) **1644004**
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number
- | Country | Priority application number (if you know it) | Date of filing (day / month / year) |
|---------|--|-------------------------------------|
|---------|--|-------------------------------------|
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application
- | Number of earlier application | Date of filing (day / month / year) |
|-------------------------------|-------------------------------------|
|-------------------------------|-------------------------------------|
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:
a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d)) **YES**

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 13

Claim(s)

Abstract

Drawing(s) 2

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 8/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

14/3/01

12. Name and daytime telephone number of person to contact in the United Kingdom

GARRY STUTTARD - 0113 2452388

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

-1-

ENCLOSURE MEMBER

The present invention relates to a multi-link conveyor chain which may be used (for example) in the glass industry, in particular to an enclosure member for protecting the integrity of the multi-link conveyor chain during use and to a method for manufacturing the multi-link conveyor chain incorporating said enclosure member.

Multi-link conveyor chains are in widespread use in the glass industry for transporting glass products between processing stations. For example, a multi-link conveyor chain which is typically 100 feet long may be used to transport blown glass from a blowing station to an annealing station. In the conventional multi-link conveyor chain, there are a plurality of parallel spaced apart elongate pins having an oval-shaped cross-section. Mounted on adjacent elongate pins are a series of link plates spaced apart along the pin by a plurality of washers, each link plate comprising a first and a second link. Each of the first and second link is capable of engaging a drive sprocket and has an oval-shaped aperture for receiving the elongate pin. The washer is typically a circular plate with a central circular aperture for receiving the pin. The primary function of the washer is to act as a spacer which permits heat to be blown through the multi-link conveyor chain to maintain the temperature of transported hot glass articles. The multi-link conveyor chain is driven by the engagement of the links of the link plate with the multiple teeth of a drive sprocket during a cycle of engagement.

The conventional multi-link conveyor chain is assembled so that each end of the elongate pin extends beyond the outermost link plate (ie beyond the edge of the flat conveyor surface) and a pin head is fixed in a conventional manner to

-2-

each exposed end. A disadvantage of this arrangement is that unless the guide strip adjacent to the multi-link conveyor chain is in perfect alignment with the edge of the multi-link conveyor chain, there is a tendency for the pin head to wear and eventually shear off so that the elongate pin may become dislodged. In extreme cases, this results in total collapse of the multi-link conveyor chain.

The present invention seeks to improve multi-link conveyor chains by enclosing one or both ends of an elongate pin in a protective enclosure member (eg a head protector). Moreover, the manufacture of such a multi-link conveyor chain enclosing both ends of an elongate pin in an enclosure member leads to particular difficulties which may be overcome in accordance with the present invention.

Thus viewed from one aspect the present invention provides a multi-link conveyor chain adapted to provide a substantially flat horizontal surface driveable between a first and a second processing station by engagement with a drive sprocket, said multi-link conveyor chain comprising:

- a plurality of elongate pins spaced apart in substantially parallel relationship including a first elongate pin adjacent to a second elongate pin, each of said elongate pins having a first end, a second end and a non-circular section, wherein the first end of each elongate pin extends beyond a first edge of the substantially flat horizontal surface;

- a plurality of link plates mounted on adjacent elongate pins having a first link connected to a second link by a connecting portion, each of the first and the second link having a substantially circular main body and a circumferentially dependent sprocket engaging member, said circular main body defining a non-circular aperture whose

-3-

shape essentially matches the non-circular section of an elongate pin;

a first enclosure member positioned at the first edge of the substantially flat horizontal surface comprising:

a main body having a substantially trapezoidal section and defining a first non-circular aperture and a second non-circular aperture, wherein the shape of the first and second non-circular aperture essentially matches the non-circular section of the first elongate pin and second elongate pin respectively and the depth of the first and second non-circular aperture is sufficient to enclose the first end of the first elongate pin and of the second elongate pin respectively; and

means for retaining the first end of the first elongate pin and the second elongate pin in the first and second non-circular aperture respectively.

In a preferred embodiment, the second end of each elongate pin extends beyond a second edge of the substantially flat horizontal surface and the multi-link conveyor chain further comprises:

a second enclosure member positioned at the second edge of the substantially flat horizontal surface comprising:

a main body having a substantially trapezoidal section and defining a first non-circular aperture and a second non-circular aperture, wherein the shape of the first and second non-circular aperture essentially matches the non-circular section of the first elongate pin and second elongate pin respectively and the depth of the first and second non-circular aperture is sufficient to enclose the second end of the first elongate pin and of the second elongate pin respectively; and

means for retaining the second end of the first elongate pin and the second elongate pin in the first and second non-circular aperture respectively.

-4-

Generally speaking, the first and second enclosure member will be identical.

By enclosing the first end of the elongate pin in a first enclosure member (and preferably the second end in a second enclosure member), the integrity of the multi-link conveyor chain is advantageously protected. In other words, the tendency for a pin head exposed beyond the edge of the conveyor surface to be sheared off is eliminated.

In a particularly preferred embodiment, the multi-link conveyor chain comprises: a plurality of enclosure members as hereinbefore defined positioned at the first and second edges of the substantially flat horizontal surface so as to enclose the first and second end of each of the plurality of elongate members.

In a preferred embodiment, the substantially trapezoidal section of the first enclosure member has a first side substantially parallel to a second side, wherein the second side is longer than the first side and has rounded corners. Preferably the first side has rounded corners (typically to a lesser extent than the second side). In use, the first enclosure member is positioned at the first edge with the second side uppermost.

In a preferred embodiment, the means for retaining comprises: a first pin head secured to the first end of the first elongate pin and a second pin head secured to the first end of the second elongate pin, said first and second pin head being seated in a counterbore in the first and second non-circular aperture of the first enclosure member respectively. Preferably the counterbore is non-tapered (eg cylindrical).

-5-

The enclosure member may be sized and configured so as to have a maximum radial extent which is equal to or less than adjacent link plates. This ensures that the enclosure member does not interfere with the substantially flat horizontal surface.

In a preferred embodiment, the circular main body of each of the first and the second link of a link plate defines a non-circular aperture whose shape non-identically matches the non-circular section of the elongate pin. The non-identical match between the non-circular section of the elongate pin and the shape of the non-circular aperture defined by the circular main body of the link causes the link plate to be advantageously driven by the elongate pin throughout the cycle of engagement with the drive sprocket.

Preferably the multi-link conveyor comprises: a plurality of elongate pins spaced apart in substantially parallel relationship including a first elongate pin adjacent to a second elongate pin which is adjacent to a third elongate pin, each of said elongate pins having a first end, a second end and a non-circular section, wherein a plurality of link plates are consecutively mounted in a staggered fashion along the first, second and third elongate pin.

In a preferred embodiment, the circumferentially dependent sprocket engaging member of each of the first and second link of the link plate is substantially flat edged. Preferably each of the first and second link of the link plate has a flat-edged, substantially teardrop profile.

Link plates may be mounted consecutively along an elongate pin and spaced apart by one or more washers. The main body of the or each washer may define a circular or non-circular aperture. In a preferred embodiment of the

-6-

invention, each washer comprises a main body defining a non-circular aperture for receiving the elongate pin whose shape essentially matches the non-circular section of the elongate pin. The essential match between the non-circular section of the elongate pin and the shape of the non-circular aperture defined by the main body of the washer renders the washer advantageously stationary throughout the cycle of engagement with the drive sprocket.

In a particularly preferred embodiment, each washer comprises a main body defining a non-circular aperture for receiving the elongate pin whose shape essentially matches the non-circular section of the elongate pin and the circular main body of each of the first and the second link of the link plate defines a non-circular aperture whose shape non-identically matches the non-circular section of the elongate pin whereby relative articulation between the washer and the link plate is thought to be responsible for an advantageous self cleaning effect.

In a particularly preferred embodiment, the non-circular aperture defined by the main body of the washer is an identical match (ie in shape and size) to the non-circular section of the elongate pin. This has the added advantage that debris is largely prevented from reaching the non-circular aperture defined by the link plate thereby preventing added wear between the aperture and the elongate pin.

Preferably the non-circular section of the elongate pin is substantially elliptical (or oval). Preferably the non-circular aperture defined by the circular main body of the (or each) link is substantially elliptical (or oval) with an enlarged side portion. Particularly preferably the enlarged side portion extends inwardly towards the connecting portion.

-7-

Preferably the non-circular aperture of the washer is substantially elliptical (or oval).

In a preferred embodiment, each washer comprises: a substantially circular main body having one or more circumferential irregularities.

Advantageously, each circumferential irregularity extends away from the circumference to a sharp axial edge. A sharp axial edge has the advantage that it cuts into (and therefore breaks up) debris whereas a worn or radiussed edge simply rubs (and therefore accumulates) debris.

Preferably, each circumferential irregularity is a substantially triangular extension.

In a preferred embodiment, the washer has a plurality of circumferential irregularities. For example, the washer has three or more circumferential irregularities, preferably five or more circumferential irregularities, particularly preferably seven or more circumferential irregularities and especially preferably about ten circumferential irregularities.

The substantially circular main body of the washer having one or more circumferential irregularities may adopt any convenient non-circular profile such as a polygonal profile (eg triangular, square, etc) or a non-polygonal profile. Typically the non-circular profile is axially symmetrical.

A non-polygonal profile may comprise a multi-sided polygon with a triangular extension on one or more (preferably all) of the sides. Preferred is a non-polygonal

-10-

Whilst it is relatively straightforward to enclose the first end of an elongate pin in the first enclosure member and thereafter to secure a second pin head to a free second end of the elongate pin using the method of the invention, it is less straightforward to secure a second pin head to the second end of the elongate pin when the second end is fitted with a second enclosure member. This is due to the space constraints imposed on the second pin head by the non-circular aperture in the second enclosure member.

Thus in a preferred embodiment of the method of the invention, in step (C) the elongate pin is inserted to a position where the first pin head is seated in a counterbore in the first non-circular aperture of the first enclosure member, said method further comprising:

(E) inserting the second end of the elongate pin into the first non-circular aperture defined by the main body of the second enclosure member to a position where the second end is enclosed within the first non-circular aperture; and

(F) eccentrically spin rivetting a piece of material (eg carbide) onto the second end of the elongate pin to produce a second pin head.

Preferably, in step (E) the elongate pin is inserted to a position in which the second end is adjacent a counterbore. In this embodiment, step (F) produces a second pin head seated in the counterbore.

Preferably, the piece of material in step (F) is greater in diameter than the desired diameter of the second pin head. Typically the second pin head is oval and the desired diameter is the length of the major axis. By way of example, where the desired diameter is between 6.0 and 6.3mm and the counterbore is of 6.5mm diameter, a piece of carbide of diameter 6.3mm is spin rivetted at an eccentricity of

-11-

about 0.05mm to produce a second pin head seated in the counterbore.

The present invention will now be described in a non-limitative sense with reference to the accompanying Figures in which:

Figure 1 illustrates an embodiment of the enclosure member of the invention; and

Figure 2 illustrates an embodiment of the multi-link conveyor assembly of the invention.

Figure 1 illustrates an embodiment of the enclosure member of the invention designated generally by reference numeral 1. The enclosure member 1 comprises a trapezoidal main body 2 having a long side 3 parallel to a short side 4. The corners 3a and 3b of the long side 3 are rounded off (and to a lesser extent so are the corners 4a and 4b of the short side 4). The main body 2 defines a first non-circular aperture 5 and a second non-circular aperture 6, each of which are elliptical and provided with a cylindrical counterbore 5a and 6a respectively.

Figure 2 illustrates in partial view an embodiment of the multi-link conveyor chain of the invention designated generally by reference numeral 11. For the sake of clarity, the elongate pins and washers are omitted from Figure 2 (nevertheless it will be readily apparent how and where these are used).

The multi-link conveyor chain 11 provides a flat surface 12 upon which may be carried articles such as glass bottles to a processing station. The multi-link conveyor chain 11 comprises a series of elongate pins of elliptical section upon which are mounted a number of link plates 14.

-13-

elongate pin may be protected using first and second enclosure members.

Figw 1

